

## VOLTAGE TESTER 3002 / 3003



### FEATURES

- AC/DC Voltage tester 12...690 V AC/DC
- TÜV / GS certification (only 3002)
- Overvoltage category CAT III 600 V, CAT IV 300 V
- Continuity test function with optical and acoustical indication
- Integrated single pole test
- Automatic detection of polarity
- Display equipped with bright shining LEDs
- Shockproof and ergonomic housing
- Fast one-hand operation for test sockets with 19 mm spacing
- Probe-tip protection

### SCOPE OF SUPPLY

- 1 pc HDT Voltage tester 3002 or 3003
- 2 pcs Batteries 1,5V AAA
- 1 pc Instruction manual
- 1 pc Carton packaging

### TECHNICAL DATA

Model	3002	3003
Display	11 LEDs (+12 V, -12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V, Single Pole, Continuity), ELV (only 3002)	
Voltage Range	12...690V AC/DC	
Polarity Indication	automatic	
Frequency Range	0...65 Hz	
Input current	< 3,5 mA	<3,5 mA (690V AC L-L) <5 mA (690V DC)
Single Pole Voltage	100...690V	
Continuity/Diode Test	optical / acoustical	
Measurement category	CAT III / 600V, CAT IV / 300V	
Protection Degree	IP 54	
In compliance with	EN 61010, EN 61243-3:2014	
Certification	TÜV GS	CE
Battery test	Connect both tips	
Batteries	2 x 1,5V AAA, LR03	2 x 1,5V AAA, R03
Length of cable	approx. 1,2 m	approx. 1 m
Dimension	approx. 205 x 67 x 27 mm	
Weight	approx. 130 g	