

SOCKET TESTER PRO 8411/8412/8413



FEATURES

- Check for correct / incorrect wiring of Schuko sockets with output of the result directly on the LCD (eg. „L and N are interchanged“, without cryptic decoding of LED codes!)
- LCD-Display with backlight
- Voltage test 230V AC (195.5V - 253V AC, 50Hz ±3%)
- Variable RCD test: RCD trip with adjustable nominal fault current 10 - 30 - 100 - 300 - 500mA (only 8412/8413)
- Measurement trip time (only 8413)
- PE error indication using built-in capacitive sensor
- PE errors are clearly signaled by the LCD display
- The fixed, flexible power plug enables quick and easy testing

SCOPE OF SUPPLY

- 1 pc. HDT Socket tester PRO 8411 or 8412
- 1 pc. Instruction Manual
- 1 pc. Carton Packaging
- 2 pc. AAA Batteries

TECHNICAL DATA

Model	8411	8412	8413
Nominal voltage	230V (- 15 % ÷ + 10%) (wenn PE nicht offen)		
RCD Test current	-	10, 30, 100, 300, 500 mA (± 15 %)	
RCD Test time	-	TRCD 200 ms (± 15 %)	
Trip time display	-	-	3 digits
PE error	> 50V (against earth)		
In compliance with	IEC / EN 61010-1		
Certification	CE		
Measurement category	CAT III / 300 V		
IP rating	IP40		
Pollution degree	2		
Battery	2 x 1,5 V / AAA		
Automatic Power Off	15 minutes		