

CURRENT VOLTAGE TESTER 3613 IP2X



The Swiss Pocket Knive for the Electrician

FEATURES

- Slim shape and size to fit in cargo pants pocket
- Measurement of voltage (...1000 V AC, 1500 V DC), current (...200 A AC/DC), resistance (...100 k Ω), frequency, continuity and rotary field
- Non-contact and single pole voltage indication
- Voltage indication by LED chain in jaw and LCD /w backlight
- Test tip fixture @ front with 19 mm distance to fit sockets
- Bright torch light in front
- Vibration motor and buzzer for safe feedback in any environment
- · Various patents applied

SCOPE OF SUPPLY

- 1 x Current Voltage Tester 3613
- 2 x AAA battery
- 1 x User manual

TECHNICAL DATA

Model	Current Voltage Tester 3613
LCD with back light	7 segment 4 digit display, NCV, Polarity, AC/DC, Hold, Frequency, Diode, Continuity, Low Voltage, Current, Low bat, LowContinuity
LEDs	Continuity, ELV/ Single Pole, Rotary Field +120 V, -120 V, 230 V, 400 V, 690 V, 1000 V
Voltage Measurement	11000 V AC TRMS, 11500 V DC, Resolution 0.1 V
Vibration motor	yes
Auto Start Options	Voltage, Continuity
Current Measurement	0,1200 A AC/DC, 4565 Hz Resolution 0,1 A
Single Pole Phase Test	>90 V1000 V ±10%, 50/60 Hz
Phase Rotation Test	1001000 V ±10% (L-L), 50/60 Hz
Resistance measurement	0100 k Ω Resolution 1 Ω <2 k Ω ; 1 k Ω >2 k Ω
Continuity Test	${<}500k\Omega,$ Continuity buzzer in resistance mode: ${<}20\Omega$
Diode test	Continuity test
Cable break detector by NCV	yes, with sensitivity bargraph and different sound patterns
Frequency Measurement	yes, 0-800 Hz
Torch light	yes
Self test	yes
Duty Cycle	30 sec on / 240 sec off
Current Consumption	<3.5 mA @ 1000 V AC
Low bat indication	yes
Auto Power Off	yes
Test leads	IP2X test tips with 19mm distance Storage on back side
Fork opening	14 mm
in compliance with	IEC 61243-3:2014, IEC 61010-1:2010
Certificate	CE
IP protection	64
Overvoltage Category	CAT IV/600 V, CAT III/1000 V
Power Supply	2 x 1.5 V AAA